

# ROOF & GUTTER SEALANT



Roof & Gutter Sealant is a single component bitumen based caulk which cures by the evaporation of solvent to form a durable plastic seal. It is ideal for a wide range of sealing and weatherproofing applications related to roofing, guttering and for emergency repairs to roofs, gutters, chimneys etc. It is ideal for sealing leaks in downpipes, guttering and flashing and can also be used to bed shingles, roof sheets and felts.

**BITUMEN BASED CAULK**  
**WEATHERPROOF SEALING**  
**SEALING & JOINTING GUTTERING**  
**EMERGENCY REPAIRS**



**TECHNICAL INFORMATION:**

| PRODUCT INFORMATION      |                                              |
|--------------------------|----------------------------------------------|
| FORM:                    | Black Paste                                  |
| SPECIFIC GRAVITY:        | 1.3 g/ml                                     |
| SKINNING TIME:           | 15 hours                                     |
| FULL CURE:               | 1-2 weeks                                    |
| FLASH POINT:             | >21°C <55°C                                  |
| TEMPERATURE RESISTANCE   | -20 to + 80°C                                |
| APPLICATION TEMPERATURE: | + 5 to + 40°C                                |
| COVERAGE:                | 12m coverage using a 5mm bead per cartridge. |

## **DIRECTIONS FOR USE:**

### **PREPARATION**

Surfaces must be clean, free of dust, loose gravel, grease, oil and other kinds of pollution. A completely dry surface is not necessary.

### **APPLICATION**

Surfaces to be sealed must be clean, sound and free from gravel, dust, oil or grease. Porous surfaces should be dry. Remove cartridge tip with a sharp knife. Cut nozzle to required size and angle. Using skeleton gun, apply sealant continuously, ensuring full contact with all surfaces. Skin over time is approx. 15 hours. Excess sealant may be removed with a cloth dipped in white spirit. Tools etc may be cleaned with white spirit. Among others not recommended include locations subject to continuous water immersion, for aquaria, PE, PP or Teflon. Adhesion tests prior to the application are recommended. It is the user's responsibility to determine suitability. It is the user's responsibility to correctly dispose of used packaging.

### **CLEANING**

Excess sealant can be removed with a cloth dipped in White Spirit or trimmed with a knife when dry. Tools can be cleaned using White Spirit. Hands can be cleaned with soap and water. Seal cartridge with overcap to ensure unused sealant remains usable.

### **IMPORTANT**

Flammable; Harmful; Keep container tightly closed; Do not empty into drains. Consult Safety Datasheet before use.

### **STORAGE**

Store in manufacturer's containers in a cool, dry, well ventilated and frost free place.

### **SHELF LIFE**

12 months in manufacturers unopened containers unused sealant remains unusable for up to 3 months.

### **PACKAGING**

310ml cartridges.