

Product Traditional Super Satinwood Base D
 Revision date 12 October 2021
 Revision 2



Safety Data Sheet (SDS)
 according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	Traditional Super Satinwood Base D
Other means of identification	UFI: 7N8X-5ES8-020A-TK35

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Paint or paint related material.
Uses advised against	No uses advised against are identified.

1.3 Details of the supplier of the safety data sheet

Supplier	FSW Coatings Ltd Virginia Co Cavan Ireland Tel: 353 49854 7209 info@fsw.ie
Contact person	

1.4 Emergency telephone number

Emergency telephone	+ 353 49854 7209 (Between 0900 and 1700 hrs Monday-Friday)
National emergency telephone number	Outside those hours, contact National Poisons Information Centre, Beaumont Hospital. Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)	
Physical and chemical hazards	Flam. Liq 3- H226
Human health	Eye Irrit.2A - H319
Environment	Not classified

2.2 Label elements

Contains	Not applicable
-----------------	----------------

Label in accordance with (EC) no. 1272/2008	 
--	---

Signal word	Warning
--------------------	---------

Hazard statements	H226 Flammable liquid and vapour. H319 Causes serious eye irritation.
--------------------------	--

Precautionary statements	Prevention P210 Keep away from heat/ sparks/open flames/hot surfaces. — No smoking. P233 Keep container tightly closed. P280 Wear protective gloves/ protective clothing/eye protection/face protection. Response P370 + P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction. Storage P403 + P235 Store in a well-ventilated place. Keep cool. Disposal
---------------------------------	--

P501 Dispose of contents/ container to a licensed hazardous waste disposal facility in accordance with all applicable regulations.

EUH statements

EUH208 Contains Cobalt bis(2-ethylhexanoate). May produce an allergic reaction.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

None known.

Section 3: Composition/information on ingredients

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product identifier	Regulation (EC) No 1272/2008	%
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	CAS-No.: 14807-96-6 EC No.: 238-877-9		20-30%
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: EC No.: 919-857-5	Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336	10-20%
titanium dioxide	CAS-No.: 13463-67-7 EC No.: 236-675-5 REACH Reg No.: 01-2119489379-17-0002		5-10%
1-methoxy-2-propanol	CAS-No.: 107-98-2 EC No.: 203-539-1	Flam. Liq 3- H226, STOT SE 3 - H336	1-5%
2-ethylhexanoic acid, zirconium salt	CAS-No.: 22464-99-9 EC No.: 245-018-1	Repr. 2 - H361d	0.1-0.9%
Isopropoxyethanol	CAS-No.: 109-59-1 EC No.: 203-685-6 REACH Reg No.: 1-2119494720-35-xxxx	Acute Tox 4 - H312, Acute Tox 4 - H332, Skin Irrit.2 - H315, Eye Irrit.2A - H319, Flam. Liq 3- H226	0.1-0.9%
Cobalt bis(2-ethylhexanoate)	CAS-No.: 136-52-7 EC No.: 205-250-6 REACH Reg No.: 01-2119524678-29-XXXX	Eye Irrit.2A - H319, Skin. Sens 1 A- H317, Repr. 1B- H360, Aquatic Acute 1 - H400, Aquatic Chronic 3 - H412	0.1-0.9%
nonane	CAS-No.: 111-84-2 EC No.: 203-913-4	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336	<0.1%
Ethanol	CAS-No.: 64-17-5 EC No.: 200-578-6 REACH Reg No.: 01-2119457610-43	Eye Irrit.2A - H319, Flam. Liq 2- H225	<0.1%
Naphthalene	CAS-No.: 91-20-3 EC No.: 202-049-5 REACH Reg No.: 01-2119561346-37-XXXX	Acute Tox 4 - H302, Carc. 2 - H351, Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410	<0.1%
propionic acid	CAS-No.: 79-09-4 EC No.: 201-176-3	Skin Corr. 1B - H314	<0.1%
octane	CAS-No.: 111-65-9 EC No.: 203-892-1	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 2- H225, STOT SE 3 - H336	<0.1%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.
Propionic Acid: Specific Concentration Limits - Eye Irrit. 2; H319: 10 % ≤ C < 25 %, STOT SE 3; H335: C ≥ 10 %, Skin Corr. 1B; H314: C ≥ 25 %, Skin Irrit. 2; H315: 10 % ≤ C < 25 %.
Ethanol: Specific Concentration Limits - Eye Irrit. 2; H319: ≥ 50.
Cobalt bis(2-ethylhexanoate): M (acute) = 1.

Section 4: First aid measures

4.1 Description of first aid measures

General information	Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue.
Inhalation	If this product is inhaled and symptoms occur, move the exposed person to fresh air promptly. If breathing is difficult, give oxygen. If breathing has stopped or the exposed person experiences difficulty in breathing, administer artificial respiration and seek immediate medical assistance.
Ingestion	Rinse mouth thoroughly. Provide fresh air, warmth and rest. Do not induce vomiting. Never give anything by mouth if victim is unconscious, is rapidly losing consciousness or is convulsing. Seek medical advice (show the label where possible). If vomiting occurs, the head should be kept low so that stomach content doesn't enter the lungs.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues after rinsing.
Eye contact	Do not rub eye. Avoid contaminating unaffected eye. Remove contact lenses if present and easy to do so. Promptly wash eye(s) with plenty of water while lifting the eye lids. Rinse with a gentle stream water for at least 15 minutes. Get prompt medical attention.

4.2 Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Exposure to product spray mists may be irritating to the respiratory system. Inhalation of vapours may cause headache, fatigue, dizziness and central nervous system effects.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin contact	Prolonged contact may cause redness, irritation and dry skin. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician	Treat symptomatically.
-------------------------------	------------------------

Section 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media	Use fire-extinguishing media appropriate for surrounding materials. Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet to extinguish fire.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products	Combustion may lead to the release of harmful vapours, including but not limited to oxides of carbon.
Unusual fire & explosion hazards	The product is classified as a flammable liquid and vapour. Vapours are heavier than air and may spread near ground to sources of ignition. Do not allow to enter drains, sewers, basements and workpits, or any place where its accumulation can be dangerous.
Specific hazards	Vapours may be ignited by a spark, a hot surface or an ember. Flash back possible over considerable distance.

5.3 Advice for firefighters

Special fire fighting procedures	Ventilate closed spaces before entering them. Water spray should be used to cool containers. If possible, fight fire from protected position. Keep up-wind to avoid fumes.
Protective equipment for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Wear protective clothing as described in Section 8 of this safety data sheet. If necessary evacuate surrounding areas. Eliminate all sources of ignition. Avoid inhalation of vapours and contact with skin and eyes.
------------------------------------	--

For emergency responders

Use non-sparking hand tools and explosion proof electrical equipment. Do not touch or walk through spilled material. Read and follow manufacturer's recommendations. Do not smoke, eat or drink while using this product.

Follow safe handling advice and personal protective equipment recommendations for normal use of product.

6.2 Environmental precautions**Environmental precautions**

Prevent any material from entering drains or waterways. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3 Methods and material for containment and cleaning up**Spill clean up methods**

Prevent further leakage or spillage if safe to do so. Ventilate and evacuate the area. Eliminate all sources of ignition. Wear necessary protective equipment. Dam and absorb spillage using a spill kit, sand, earth or other non-combustible material. Prevent entry into sewers, water course, basement or confined areas. Use non sparking tools or equipment. Recover by pumping or with suitable absorbent. Place spilled material into suitable labelled sealed containers. Remove waste promptly to a safe area.

6.4 Reference to other sections**Reference to other sections**

See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.

Section 7: Handling and storage**7.1 Precautions for safe handling****Handling**

Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Wear suitable personal protective equipment, as detailed in Section 8. Keep away from heat, sparks and open flame. Formation of sparks and static electricity must be prevented. Earth all equipment. Use only non-sparking tools. Avoid contact with skin and eyes. Avoid inhalation of vapours. Do not use contact lenses. Avoid prolonged or repeated contact. Read and follow manufacturer's recommendations. Keep container tightly closed.

7.2 Conditions for safe storage, including any incompatibilities**Storage precautions**

Store in tightly closed original container in a cool, dry and well-ventilated place. Keep upright, locked up and out of reach of children. Keep away from incompatible materials (see section 10). Protect against static discharge and keep away from sources of ignition.

Storage class

Flammable liquid storage.

7.3 Specific end use(s)**Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

Usage description

Use only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection**8.1 Control parameters**

Component	STD	TWA (8 Hrs)		STEL (15mins)		Notes
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	OEL		10 mg/m ³			
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	OEL		0.8 mg/m ³			
titanium dioxide	OEL		10 mg/m ³			
titanium dioxide	OEL		4 mg/m ³			
1-methoxy-2-propanol	OEL	100 ppm	375 mg/m ³	150 ppm	568 mg/m ³	IOELV
Isopropoxyethanol	OEL	25 ppm	106 mg/m ³			Sk
nonane	OEL	200 ppm	1050 mg/m ³			
Ethanol	OEL			1000 ppm		
Naphthalene	OEL	10 ppm	50 mg/m ³			IOELV
propionic acid	OEL	10 ppm	31 mg/m ³	20 ppm	62 mg/m ³	79-09-4

octane	OEL	300 ppm	1450 mg/m ³			
--------	-----	---------	------------------------	--	--	--

Ingredient comments

Ireland, Occupational Exposure Limits 2021.

8.2 Exposure Controls**Protective equipment****Engineering measures****Respiratory equipment****Hand protection****Eye protection****Other protection****Hygiene measures****Process conditions**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Where necessary use lighting and electrical equipment designed for use in atmospheres where flammable vapours are present. Where risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN 143 should be used, and suitable respirator cartridges as a backup to engineering controls. The specific respirator selected must be based on contamination levels found in the work place. Use respiratory protection as specified by qualified professional if concentrations exceed the limits listed in Section 8. Use type ABEK (EN 14387) respirator cartridges. Consult manufacturer for specific advice.

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. Use chemical resistant gloves to minimize skin contact. Gloves must be inspected prior to use. Suggested material: Nitrile rubber. Break through time: 480 min. Layer thickness: 0.33 mm.

Consult manufacturer for advice. Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

Wear safety goggles to prevent any possibility of eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).

Protective clothing should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. The selected clothing must satisfy the European norm standard EN 943.

Observe normal hygiene standards. DO NOT SMOKE! Wash hands after use. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke.

Ensure that eye flushing systems and safety showers are located close by in the work place.

Section 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	Viscous liquid.
Colour	Various.
Odour	Hydrocarbon, (slight).
Odour threshold - lower	No information available as testing has not been completed.
Odour threshold - upper	No information available as testing has not been completed.
pH-Value, Conc. Solution	No information available as testing has not been completed.
pH-Value, Diluted solution	No information available as testing has not been completed.
Melting point	May start to solidify at the following temperature: -15°C This is based on data for the following ingredient: Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics. Weighted average: -54.16°C
Initial boiling point and boiling range	>142°C
Flash point	Closed cup 42°C
Evaporation rate	Highest known value: 0.04 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics) Weighted average: 0.03 compared with butyl acetate
Flammability state	Liquid
Flammability limit - lower(%)	Greatest known range: Lower: 0.6% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics)

Flammability limit - upper(%)	Greatest known range: Upper: 7% (Hydrocarbons, C10-C13, nalkanes, isoalkanes, cyclics, < 2% aromatics)
Vapour pressure	Highest known value: 0.1 to 0.3 kPa (0.8 to 2.3 mm Hg) (at 20°C) (Naphtha(petroleum), hydrotreated heavy). Weighted average: 0.16 kPa (1.2 mm Hg) (at 20°C)
Vapour density (air=1)	Highest known value: 4.5 (Air = 1) (Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics).
Relative density	1.20 +/- 0.2
Bulk density	No information available as testing has not been completed.
Solubility	Insoluble in cold water
Decomposition temperature	Stable under normal handling and storage conditions
Partition coefficient; n-Octanol/Water	No information available as testing has not been completed.
Auto ignition temperature (°C)	Lowest known value: >230°C (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics).
Viscosity	Kinematic (40°C): >0.21 cm ² /s
Explosive properties	Not classified as explosive.
Oxidising properties	The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight	No information available as testing has not been completed.
Volatile organic compound	299.00 g/litre
Other information	Volume solids: 60.0% +/- 1.0% Weight Solids: 73.0% +/- 1.0%

Section 10: Stability and reactivity

10.1 Reactivity

Reactivity	Keep away from incompatibles such as oxidizing agents, acids, and alkalis.
-------------------	--

10.2 Chemical stability

Stability	Stable under normal temperature conditions and recommended use.
------------------	---

10.3 Possibility of hazardous reactions

Hazardous reactions	For information on hazardous reaction see section 10.1.
Hazardous polymerisation	Unknown
Polymerisation description	Unknown.

10.4 Conditions to Avoid

Conditions to avoid	Heat, sparks, open flames, temperature extremes and direct sunlight.
----------------------------	--

10.5 Incompatible materials

Materials to avoid	Avoid contact with oxidising agents, strong alkalis, and strong acids.
---------------------------	--

10.6 Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other harmful gases or vapors.
---	---

Section 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No. 1272/2008

Toxicological information	No toxicological information for the overall finished product.
Acute toxicity (Oral LD50)	No information available as testing has not been completed.
Acute toxicity (Dermal LD50)	No information available as testing has not been completed.
Acute toxicity (Inhalation LD50)	No information available as testing has not been completed.
Serious eye damage/irritation	Causes serious eye irritation.
Skin corrosion/irritation	The product is not classified as a skin corrosion/irritation hazard.
Respiratory sensitisation	The product is not classified as a respiratory hazard.
Skin sensitisation	The product is not classified as a skin sensitisation hazard.
Germ cell mutagenicity	The product is not classified as a mutagen.
Carcinogenicity	The product is not classified as a carcinogen hazard.
Specific target organ toxicity - Single exposure:	
STOT - Single exposure	The product is not classified as a single exposure specific target organ toxin.
Specific target organ toxicity - Repeated exposure:	
STOT - Repeated exposure	The product is not classified as a repeat exposure specific target organ toxin.
Inhalation	Exposure to product spray mists may be irritating to the respiratory system. Inhalation of vapours may cause headache, fatigue, dizziness and central nervous system effects.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin contact	Prolonged contact may cause redness, irritation and dry skin. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Waste management	Contaminated packaging should be disposed of according to local authority guidelines. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not burn. When handling waste, consideration should be made to the safety precautions applying to handling of the product.
Routes of entry	Eyes, skin, ingestion or inhalation.
Target organs	Eyes, skin, digestive system, respiratory system.
Aspiration hazards:	The product is not classified as an aspiration hazard.
Reproductive toxicity:	The product is not classified as a reproductive hazard.

Name	LD50 oral	LD50 dermal	LD50 inhalation
1-methoxy-2-propanol	=4016.00mg/kg Rat		=6500.00ppmV Rat 4 Hours
nonane			3200.00ppmV Rat 4 Hours 17000.00mg/m-3 Rat 4 Hours
Isopropoxyethanol	5600.00mg/kg Rat	1440.00mg/kg Rabbit	
Ethanol	7060.00mg/kg Rat		124.70mg/l (vapours) Rat 4 Hours
Naphthalene	>2000.00mg/kg Rat	>2000.00mg/kg Rabbit	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>5000.00mg/kg Rat	>5000.00mg/kg Rabbit	>6.10mg/l (vapours) Rat 4 Hours
2-ethylhexanoic acid, zirconium salt	>5.00g/kg Rat	>5.00g/kg Rabbit	
propionic acid	2600.00mg/kg Rat	525.00mg/kg Rabbit	
titanium dioxide	10000.00mg/kg Rat		

11.2 Information on other hazards

Information on other hazards	None known.
-------------------------------------	-------------

Section 12: Ecological information

12.1 Toxicity

Acute toxicity - Fish	No information available as testing has not been completed.
Acute toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Acute toxicity - Aquatic plants	No information available as testing has not been completed.

Acute toxicity - Microorganisms	No information available as testing has not been completed.
Chronic toxicity - Fish	No information available as testing has not been completed.
Chronic toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Chronic toxicity - Aquatic plants	No information available as testing has not been completed.
Chronic toxicity - Microorganisms	No information available as testing has not been completed.
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Eco toxicological information	Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008.

12.2 Persistence and degradability

Degradability	The degradability of the product has not been stated.
Biological oxygen demand	No information available as testing has not been completed.
Chemical oxygen demand	No information available as testing has not been completed.

12.3 Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
Bioaccumulation factor	No information available as testing has not been completed.
Partition coefficient; n-Octanol/Water	No information available as testing has not been completed.

12.4 Mobility in soil

Mobility	Insoluble in cold water.
-----------------	--------------------------

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB Substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties	The product does not contain any substances with endocrine disrupting properties at a concentration above or equal to 0.1%.
--	---

12.7 Other adverse effects

Other adverse effects	None known.
------------------------------	-------------

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
1-methoxy-2-propanol	LC50 96 Hours =6812.00mg/l Leuciscus idus (Golden Orfe)	LC50 48 Hours =23000.00mg/l Daphnia magna	EC50 =1000.00mg/l Selenastrum Capricornutum
Isopropoxyethanol		EC50 48 Hours 3610.00ppm Daphnia magna	
Ethanol	LC50 96 Hours 100.00mg/l Pimephales promelas (Fat-head Minnow)		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LC50 96 Hours >100.00ppm Freshwater Fish	LC50 48 Hours >100.00ppm Daphnia magna	
propionic acid	LC50 96 Hours 51.00ppm Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours 22.70ppm Daphnia magna	EC50 96 Hours 43.00mg/l

Section 13: Disposal considerations

Waste management	Contaminated packaging should be disposed of according to local authority guidelines. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not burn. When handling waste, consideration should be made to the safety precautions applying to handling of the product.
-------------------------	--

13.1 Waste treatment methods

Disposal methods

Dispose of waste and residues in accordance with local authority requirements. For waste disposal, use a licensed industrial waste disposal agent.

Section 14: Transport information**14.1 UN number or ID number**

UN no. (ADR)	UN1263
UN no. (IMDG)	UN1263
UN no. (IATA)	UN1263

14.2 UN proper shipping name

ADR proper shipping name	PAINT or PAINT RELATED MATERIAL
IMDG proper shipping name	PAINT or PAINT RELATED MATERIAL
IATA proper shipping name	PAINT

14.3 Transport hazard class(es)

ADR class	3
IMDG class	3
IATA class	3

Transport labels**14.4 Packing group**

ADR/RID/ADN packing group	III
IMDG packing group	III
IATA packing group	III

14.5 Environmental hazards

ADR	No
IMDG	No
IATA	No

14.6 Special precautions for user

EMS	F-E, S-E
Emergency action code	A3 A72 A192
Hazard no. (ADR)	30
Tunnel restriction code	(D/E)

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Section 15: Regulatory information**15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture**

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
Approved code of practice	2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2021) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)

15.2 Chemical safety assessment

Chemical safety assessment	No chemical safety assessment has been carried out.
----------------------------	---

Section 16: Other information

General information**Revision comments**

This Safety Data Sheet is in accordance with REACH Annex II, (EC) No 2020/878.

[1]Information updated. [2]Information updated. [3]Information updated. [8]Information updated. [11]Information updated. [12]Information updated. [15]Information updated. This is a second issue.

Revision date

12 October 2021

Revision

2

Safety data sheet status

Approved.

Hazard statements in full**EUH066**

Repeated exposure may cause skin dryness or cracking.

H226

Flammable liquid and vapour.

H304

May be fatal if swallowed and enters airways.

H336

May cause drowsiness or dizziness.

H315

Causes skin irritation.

H318

Causes serious eye damage.

H361

Suspected of damaging fertility or the unborn child .

H319

Causes serious eye irritation.

H302

Harmful if swallowed.

H412

Harmful to aquatic life with long lasting effects.

H312

Harmful in contact with skin.

H332

Harmful if inhaled.

H317

May cause an allergic skin reaction.

H360

May damage fertility or the unborn child .

H400

Very toxic to aquatic life.

H411

Toxic to aquatic life with long lasting effects.

H410

Very toxic to aquatic life with long lasting effects.

H225

Highly flammable liquid and vapour.

H335

May cause respiratory irritation.

H351

Suspected of causing cancer .

H314

Causes severe skin burns and eye damage.

EUH208

Contains Cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.