

DRIVEWAY RESTORER & SEALER

Larsen Driveway Restorer & Sealer is a unique combination of acrylic polymers, inorganic pigments and fillers designed to enhance the appearance of tarmac drives. It leaves an attractive, low sheen finish, which is resistant to weather damage and staining.

HIGH PERFORMANCE COATING
MAKES OLD TARMAC LOOK LIKE NEW
TOUGH, DURABLE SEAL
QUICK DRYING TIME -
USE DRIVEWAY AFTER 4-5 HOURS



TECHNICAL INFORMATION:

PRODUCT INFORMATION	
FORM:	Coloured Liquid
COLOUR:	Black
ODOUR:	Acrylic type.
AREA OF APPLICATION:	Suitable for use on sound tarmac.
VOC CONTENT:	Low (0.30-7.99%)
MINIMUM APPLICATION TEMPERATURE:	6°C
SIZE:	5 L jerry can

DIRECTIONS FOR USE:

PREPARATION

Give the tarmac a scrub with a stiff bristle brush to remove any dust, dirt or moss. Use Larsen Decking & Paving Cleaner to give the tarmac a good clean. For any existing oil or grease stains, use this neat. Fill any holes with fresh concrete or cold cure tarmac, if needed. Make sure any cleaners are rinsed off the tarmac and its dry before you start to apply Driveway Restorer & Sealer.

APPLICATION

On cold & damp days, drying and re-coat times will take longer. For best results, use on a dry day above 10C. Give the jar a really good stir before and during use. Use a long pile roller and tray. Pour the paint into the roller tray and fully load your roller. Keep on stirring the paint during use. Paint from the furthest point. Wait 4 hours before applying on a second coat.

COVERAGE

Larsen Driveway Restorer & Sealer will cover up to 6 m² per litre per coat. Coverage rates will vary with the porosity and roughness of the surface. The level quoted is based on average performances and a site trial is recommended.

DYRING TIME

For best results, apply two coats of Larsen Driveway Restorer & Sealer, allowing 4 hours between coats. Once the second coat has been applied, cars can be parked on the drive after a further 4 hours. However, Driveway Restorer & Sealer does not reach its optimum performance levels until after a few days; and should be left overnight before subjecting to heavy use.

CLEANING OF TOOLS

All equipment should be cleaned immediately after use with water and detergent. Remove as much product as possible from application equipment before washing.

IMPORTANT NOTES

- Always read the label carefully before use
- Don't apply if it's raining or forecast to rain
- Oil and petrol spills should be removed as soon as possible with warm water.
- Allow new tarmac to dry for 90 days before applying Larsen Driveway Restorer & Sealer
- Protect from frost

STORAGE

Store in a cool, dry, well ventilated area away from heat, sources of ignition and sunlight. The shelf life of this product in airtight containers is at least 3 years. Always store in ambient conditions away from temperature extremes. Protect from frost. Store above 5°C.

HEALTH AND SAFETY

Don't empty any left over product into drains or watercourses. Your local authority may have special ways to get rid of waste coatings.

FLAMMABILITY

Flash point above 61°C. Non-flammable product.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.