

White Valu-Lay Underlay

Roll Dimensions: 1m x 2mm



Product Information

Valu-Lay underlay offers an economic solution for insulating laminate floors. Valu-Lay is produced from closed cell Polyethylene Foam which is CFC and HCFC free and 100% recyclable. The product is available in various sizes to suit most applications. Minor floor imperfections may be accommodated by using these materials. The product has very effective acoustic qualities.

Technical Data

Properties	Typical Value	Method
Roll Specifications		
Nominal Thickness	2mm $\pm$ 10%	ISO 1923
Width	1m $\pm$ 1%	ISO 1923
Length	$\pm$ 1%	ISO 1923
Roll Weight	40 g/m ²	
Apparent Density	$\approx$ 20 kg/m ³	ISO 845
Acoustic Properties		
Sound Reduction	<17dB	ISO 10140-2:2010
Thermal Properties		
Thermal Conductivity (λ) Tested at mean 10°C	0.049 W/mK	BS 4745:2005
Thermal Resistance (R - Value)	0.041 m ² K/W	BS 4745:2005
TOG	0.41	BS 4745:2005
Foam Colour / Backing	White / No Backing	
Backing Specifications	Not Applicable	

*The above information can only be regarded as typical properties rather than guaranteed values and as a result serves as reference only based on Supplier Information.

**Recommended storage conditions: do not store in direct sunlight.