

Product Fleetwood Traditional Oil Based Non-Drip Gloss
 Revision date 15 October 2021
 Revision 2



Safety Data Sheet (SDS)
 according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	Fleetwood Traditional Oil Based Non-Drip Gloss
Other means of identification	UFI: GS9X-RERD-Y20S-D0P0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Paint or paint related material.
Uses advised against	Any other purpose.

1.3 Details of the supplier of the safety data sheet

Supplier	FSW Coatings Ltd Virginia Co Cavan Ireland Tel: 353 49854 7209 info@fsw.ie
Contact person	

1.4 Emergency telephone number

Emergency telephone	+ 353 49854 7209 (Between 0900 and 1700 hrs Monday-Friday)
National emergency telephone number	Outside those hours, contact National Poisons Information Centre, Beaumont Hospital. Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)	
Physical and chemical hazards	Flam. Liq 3- H226
Human health	Skin. Sens 1 A- H317
Environment	Not classified

2.2 Label elements

Contains	Cobalt bis(2-ethylhexanoate)
-----------------	------------------------------

Label in accordance with (EC) no. 1272/2008



Signal word	Warning
--------------------	---------

Hazard statements	H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction.
--------------------------	--

Precautionary statements	Prevention P210 Keep away from heat/ sparks/open flames/hot surfaces. — No smoking. P233 Keep container tightly closed. P280 Wear protective gloves/ protective clothing/eye protection/face protection.
	Response

P370 + P378 In case of fire: Use carbon dioxide, foam or powder for extinction.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal

P501 Dispose of contents/ container to a licensed hazardous waste disposal facility in accordance with all applicable regulations.

EUH statements

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

None known.

Section 3: Composition/information on ingredients

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product identifier	Regulation (EC) No 1272/2008	%
titanium dioxide	CAS-No.: 13463-67-7 EC No.: 236-675-5 REACH Reg No.: 01-2119489379-17-XXXX		20-30%
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: EC No.: 919-857-5 REACH Reg No.: 01-2119463258-33-XXXX	Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336	5-10%
propane-1,2-diol	CAS-No.: 57-55-6 EC No.: 200-338-0 REACH Reg No.: 01-2119456809-23-0000		1-5%
2-ethylhexanoic acid, zirconium salt	CAS-No.: 22464-99-9 EC No.: 245-018-1	Repr. 2 - H361d	0.1-0.9%
Cobalt bis(2-ethylhexanoate)	CAS-No.: 136-52-7 EC No.: 205-250-6 REACH Reg No.: 01-2119524678-29-XXXX	Eye Irrit.2A - H319, Skin. Sens 1 A- H317, Repr. 1B- H360, Aquatic Acute 1 - H400, Aquatic Chronic 3 - H412	0.1-0.9%
nonane	CAS-No.: 111-84-2 EC No.: 203-913-4	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336	<0.1%
propionic acid	CAS-No.: 79-09-4 EC No.: 201-176-3	Skin Corr. 1B - H314	<0.1%
octane	CAS-No.: 111-65-9 EC No.: 203-892-1	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 2- H225, STOT SE 3 - H336	<0.1%
pentaerythritol	CAS-No.: 115-77-5 EC No.: 204-104-9		<0.1%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

Propionic acid: Specific Concentration limits - Eye Irrit. 2; H319: 10 % to < 25 %; STOT SE 3; H335:10 %; Skin Corr. 1B; H314: 25 %; Skin Irrit. 2; H315: 10 % to < 25 %.

Cobalt bis(2-ethylhexanoate): M (acute) = 1.

Section 4: First aid measures

4.1 Description of first aid measures

General information

Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all burns and eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue.

Inhalation

If this product is inhaled and symptoms occur, move the exposed person to fresh air promptly. If breathing has stopped or the exposed person experiences difficulty in breathing,

Ingestion	administer artificial respiration and seek immediate medical assistance. Seek medical attention if symptoms persist. If this product is ingested, immediately rinse mouth and drink plenty of water. If person becomes uncomfortable or if ingested in large amounts seek medical advice and bring these instructions. Never give anything by mouth to an unconscious person. Ingestion is not believed to be a likely route of exposure.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with water. Get medical attention promptly if symptoms occur after washing.
Eye contact	If this product contacts the eyes, gently flush eyes with water for at least fifteen (15) minutes, lifting the upper and lower eyelids occasionally. Remove contact lenses if present and easy to do so. Avoid contaminating unaffected eye. Seek medical attention if irritation persists.

4.2 Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Exposure to product spray mists may be irritating to the respiratory system. May cause drowsiness or dizziness.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin contact	Prolonged contact may cause redness, irritation and dry skin. May cause an allergic skin reaction.
Eye contact	May cause temporary eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician	Treat symptomatically.
-------------------------------	------------------------

Section 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media	Use fire-extinguishing media appropriate for surrounding materials. Carbon dioxide, foam or powder-fire extinguisher.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products	Burning produces obnoxious and toxic fumes. Incomplete combustion may form carbon monoxide.
Unusual fire & explosion hazards	FLAMMABLE. Exposure to fire may cause containers to rupture/explode. Do not allow to enter drains, sewers, basements and workpits, or any place where its accumulation can be dangerous.
Specific hazards	Vapours may be ignited by a spark, a hot surface or an ember. When heated and in case of fire, harmful vapours/gases may be formed.

5.3 Advice for firefighters

Special fire fighting procedures	Avoid breathing fire vapours. Keep up-wind to avoid fumes. Fight advanced or massive fires from safe distance or protected location. If possible, fight fire from protected position.
Protective equipment for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Do not smoke, eat or drink while using this product. Eliminate all sources of ignition. Wash hands after use. Follow precautions for safe handling described in this safety data sheet. Read and follow manufacturer's recommendations. If necessary evacuate surrounding areas. Do not wear contact lenses while using this product. Do not mix with other chemicals.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Follow safe handling advice

recommendations for normal use of product. DO NOT use equipment in clean-up procedure which may produce sparks. Eliminate all sources of ignition, ventilate area, evacuate personnel.

6.2 Environmental precautions

Environmental precautions

Avoid release to the environment. Do not discharge into drains, water courses or onto the ground.

6.3 Methods and material for containment and cleaning up

Spill clean up methods

Eliminate all sources of ignition. Ventilate area. Keep area evacuated and free from ignition sources until product has evaporated. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container. Dam and absorb spillage using a spill kit, sand, earth or other non-combustible material. Use non sparking tool/equipments. Wash the spill site with water.

6.4 Reference to other sections

Reference to other sections

See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.

Section 7: Handling and storage

7.1 Precautions for safe handling

Handling

Wear suitable personal protective equipment, as detailed in Section 8. Ensure adequate ventilation. Keep away from heat, sparks and open flame. Formation of sparks and static electricity must be prevented.

Avoid spilling, skin and eye contact. Avoid inhalation of vapours. Do not mix with other chemicals. Earth all equipment. Read and follow manufacturer's recommendations.

7.2 Conditions for safe storage, including any incompatibilities

Storage precautions

Keep containers tightly closed. Keep in original container. Keep away from heat, sparks and open flame. Protect from sunlight. Do not expose to temperatures exceeding 50 C. Keep out of the reach of children.

Storage class

Flammable liquid storage.

7.3 Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.

Usage description

Use only according to directions. For use in washrooms only.

Section 8: Exposure controls/Personal protection

8.1 Control parameters

Component	STD	TWA (8 Hrs)		STEL (15mins)		Notes
titanium dioxide	OEL		10 mg/m ³			
titanium dioxide	OEL		4 mg/m ³			
propane-1,2-diol	OEL	150 ppm	470 mg/m ³			
propane-1,2-diol	OEL		10 mg/m ³			
nonane	OEL	200 ppm	1050 mg/m ³			
propionic acid	OEL	10 ppm	31 mg/m ³	20 ppm	62 mg/m ³	IOELV
octane	OEL	300 ppm	1450 mg/m ³			
pentaerythritol	OEL		10 mg/m ³		20 mg/m ³	
pentaerythritol	OEL		4 mg/m ³			

Ingredient comments

Ireland, Occupational Exposure Limits 2021.

8.2 Exposure Controls

Protective equipment



Engineering measures	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.
Respiratory equipment	Use respiratory protection as specified by an industrial hygienist or other qualified professional. Use type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. Use respirators and components tested and approved under appropriate government standards such as CEN (EU).
Hand protection	Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Change gloves regularly. Suggested material: Nitrile rubber gloves. Minimum layer thickness: 0.33 mm. Breakthrough time: > 480 min. Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374. Gloves must be selected according to the application and duration of use at the workstation. Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.
Eye protection	Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).
Other protection	Protective clothing should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. The selected clothing must satisfy the European norm standard EN 943.
Hygiene measures	DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.
Process conditions	Keep container tightly sealed when not in use. Provide eyewash station. Use only according to directions.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	White
Odour	Slight Hydrocarbon.
Odour threshold - lower	No information available.
Odour threshold - upper	No information available.
pH-Value, Conc. Solution	Not applicable.
pH-Value, Diluted solution	Not applicable.
Melting point	Melting/freezing point May start to solidify at the following temperature: -15°C This is based on data for the following ingredient: Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics. Weighted average: -58.56°C
Initial boiling point and boiling range	>142°C
Flash point	Closed cup 42°C
Evaporation rate	Highest known value: 0.04 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics) Weighted average: 0.03 compared with butyl acetate
Flammability state	Liquid
Flammability limit - lower(%)	Lower: 0.6% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
Flammability limit - upper(%)	Upper: 7% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics)

Vapour pressure	Highest known value: 0.1 to 0.3 kPa (0.8 to 2.3 mm Hg) (at 20°C) (Naphtha(petroleum), hydrotreated heavy). Weighted average: 0.16 kPa (1.2 mm Hg) (at 20°C)
Vapour density (air=1)	Highest known value: 4.5 (Air = 1) (Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics).
Relative density	1.15 +/- 0.2
Bulk density	No information available.
Solubility	Insoluble in cold water
Decomposition temperature	Stable under normal handling and storage conditions
Partition coefficient; n-Octanol/Water	No information available as testing has not been completed.
Auto ignition temperature (°C)	Lowest known value: >230°C (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics).
Viscosity	Kinematic (40°C): >0.31 cm ² /s
Explosive properties	Not classified as explosive.
Oxidising properties	The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight	No information available.
Volatile organic compound	288.00 g/litre
Other information	Volume solids: 63.0% +/- 1.0% Weight Solids: 74.0 +/- 1.0%

Section 10: Stability and reactivity

10.1 Reactivity

Reactivity	Reaction with strong acids, strong alkalis and oxidising materials.
-------------------	---

10.2 Chemical stability

Stability	Stable under normal temperature conditions and recommended use.
------------------	---

10.3 Possibility of hazardous reactions

Hazardous reactions	For information on hazardous reaction see section 10.1.
Hazardous polymerisation	Unknown
Polymerisation description	Unknown.

10.4 Conditions to Avoid

Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid exposure to high temperatures or direct sunlight.
----------------------------	---

10.5 Incompatible materials

Materials to avoid	Keep away from strong oxidizing agents, strong acids and strong caustics.
---------------------------	---

10.6 Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other harmful gases or vapors.
---	---

Section 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No. 1272/2008**

Toxicological information	No toxicological information for the overall finished product.
Acute toxicity (Oral LD50)	No information available as testing has not been completed.
Acute toxicity (Dermal LD50)	No information available as testing has not been completed.
Acute toxicity (Inhalation LD50)	No information available as testing has not been completed.
Serious eye damage/irritation	Product is not classified as an eye irritant.
Skin corrosion/irritation	The product is not classified as a skin corrosion/irritation hazard.
Respiratory sensitisation	The product is not classified as a respiratory hazard.
Skin sensitisation	The product is classified as a skin sensitisation hazard.
Germ cell mutagenicity	The product is not classified as a mutagen.
Carcinogenicity	The product is not classified as a carcinogen hazard.
Specific target organ toxicity - Single exposure:	
STOT - Single exposure	The product is not classified as a single exposure specific target organ toxin.
Specific target organ toxicity - Repeated exposure:	
STOT - Repeated exposure	The product is not classified as a repeat exposure specific target organ toxin.
Inhalation	Exposure to product spray mists may be irritating to the respiratory system. May cause drowsiness or dizziness.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin contact	Prolonged contact may cause redness, irritation and dry skin. May cause an allergic skin reaction.
Eye contact	May cause temporary eye irritation.
Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product. Handle in accordance with good industrial hygiene and safety practice. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not burn.
Routes of entry	Eyes, skin, ingestion or inhalation.
Target organs	Eyes, skin, digestive system, respiratory system.
Aspiration hazards:	The product is not classified as an aspiration hazard.
Reproductive toxicity:	The product is not classified as a reproductive hazard.

Name	LD50 oral	LD50 dermal	LD50 inhalation
propane-1,2-diol	22000.00mg/kg Rat	>2000.00mg/kg Rabbit	
nonane			3200.00ppmV Rat 4 Hours17000.00mg/m-3 Rat 4 Hours
propionic acid	2600.00mg/kg Rat	525.00mg/kg Rabbit	
octane			25260.00ppmV Rat 4 Hours118.00g/m3 Rat 4 Hours
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>5000.00mg/kg Rat	>5000.00mg/kg Rabbit	>6.10mg/l (vapours) Rat 4 Hours
2-ethylhexanoic acid, zirconium salt	>5.00g/kg Rat	>5.00g/kg Rabbit	

11.2 Information on other hazards

Information on other hazards	None known.
-------------------------------------	-------------

Section 12: Ecological information**12.1 Toxicity**

Acute toxicity - Fish	No information available as testing has not been completed.
Acute toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Acute toxicity - Aquatic plants	No information available as testing has not been completed.
Acute toxicity - Microorganisms	No information available as testing has not been completed.
Chronic toxicity - Fish	No information available as testing has not been completed.

Chronic toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Chronic toxicity - Aquatic plants	No information available as testing has not been completed.
Chronic toxicity - Microorganisms	No information available as testing has not been completed.
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Eco toxicological information	Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008.

12.2 Persistence and degradability

Degradability	The degradability of the product has not been stated.
Biological oxygen demand	No information available as testing has not been completed.
Chemical oxygen demand	No information available as testing has not been completed.

12.3 Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
Bioaccumulation factor	No information available as testing has not been completed.
Partition coefficient; n-Octanol/Water	No information available as testing has not been completed.

12.4 Mobility in soil

Mobility	Insoluble in cold water.
-----------------	--------------------------

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product is not identified as a PBT/vPvB substance.

12.6 Endocrine disrupting properties

Endocrine disrupting properties	The product does not contain any substances with endocrine disrupting properties at a concentration above or equal to 0.1%.
--	---

12.7 Other adverse effects

Other adverse effects	None known.
------------------------------	-------------

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
propane-1,2-diol	LC50 96 Hours 40613.00mg/l Onchorhynchus mykiss (Rainbow Trout)		
propionic acid	LC50 96 Hours 51.00ppm Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours 22.70ppm Daphnia magna	EC50 96 Hours 43.00mg/l
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LC50 96 Hours >100.00ppm Freshwater Fish	LC50 48 Hours >100.00ppm Daphnia magna	

Section 13: Disposal considerations

Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product. Handle in accordance with good industrial hygiene and safety practice. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not burn.
-------------------------	---

13.1 Waste treatment methods

Disposal methods	Dispose of waste and residues in accordance with local authority requirements, and in accordance with the European Directives on waste and hazardous waste. Waste must be classified and labelled prior to recycling or disposal. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.
-------------------------	--

Section 14: Transport information**14.1 UN number or ID number**

UN no. (ADR)	UN1263
UN no. (IMDG)	UN1263
UN no. (IATA)	UN1263

14.2 UN proper shipping name

ADR proper shipping name	PAINT or PAINT RELATED MATERIAL
IMDG proper shipping name	PAINT or PAINT RELATED MATERIAL
IATA proper shipping name	PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

ADR class	3
IMDG class	3
IATA class	3

Transport labels

**14.4 Packing group**

ADR/RID/ADN packing group	III
IMDG packing group	III
IATA packing group	III

14.5 Environmental hazards

ADR	No
IMDG	No
IATA	No

14.6 Special precautions for user

EMS	F-E, S-E
Emergency action code	A3 A72 A192
Hazard no. (ADR)	30
Tunnel restriction code	(D/E)

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Section 15: Regulatory information**15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture**

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
Approved code of practice	2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2021) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)

15.2 Chemical safety assessment

Chemical safety assessment	No chemical safety assessment has been carried out.
----------------------------	---

Section 16: Other information

General information	This Safety Data Sheet is in accordance with REACH Annex II, (EC) No 2020/878.
Revision comments	[1]Information updated. [2]Information updated. [3]Information updated. [4]Information updated. [5]Information updated. [6]Information updated. [7]Information updated. [8]Information updated. [9]Information updated. [10]Information updated. [11]Information updated. [12]Information updated. [15]Information updated. This is a second issue.
Revision date	15 October 2021
Revision	2
Safety data sheet status	Approved.

Hazard statements in full

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.
H361	Suspected of damaging fertility or the unborn child .
H317	May cause an allergic skin reaction.
H360	May damage fertility or the unborn child .
H400	Very toxic to aquatic life.
H315	Causes skin irritation.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H314	Causes severe skin burns and eye damage.
H225	Highly flammable liquid and vapour.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.