

Product Fleetwood Ultra Tough Yacht Varnish Gloss
 Revision date 20 February 2019
 Revision 2



Safety Data Sheet (SDS)
 according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	Fleetwood Ultra Tough Yacht Varnish Gloss
Other means of identification	W75X-XE5C-R20H-AWSK

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Paint or paint related material.
Uses advised against	No uses advised against are identified.

1.3 Details of the supplier of the safety data sheet

Supplier	FSW Coatings Ltd. Virginia Co Cavan Ireland Tel: 353 49854 7209 info@fsw.ie
Contact person	

1.4 Emergency telephone number

Emergency telephone	+ 353 49854 7209 (Between 0900 and 1700 hrs Monday-Friday)
National emergency telephone number	Outside those hours, contact National Poisons Information Centre, Beaumont Hospital. Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)	Flam. Liq 3- H226
Physical and chemical hazards	Skin. Sens 1 - H317, STOT SE 3 - H336
Human health	Not classified
Environment	

2.2 Label elements

Contains	reaction mass of ?-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl-propionyl)-?-hydroxypoly(oxyethylene) and ?-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-?-3-(3-(2H-benzotriazol-2-yl)-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) Butanone oxime Cobalt bis(2-ethylhexanoate) nonane
-----------------	---

Label in accordance with (EC) no. 1272/2008



Signal word	Warning
--------------------	---------

Hazard statements	H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.
--------------------------	---

Precautionary statements**Prevention**

P210 Keep away from heat/ sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/eye protection/face protection.

Response

P370 + P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

2.3 Other hazards

None known.

Section 3: Composition/information on ingredients**3.1 Substance**

Not applicable.

3.2 Mixtures

Name	Product identifier	Regulation (EC) No 1272/2008	%
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS-No.: 64742-48-9 EC No.: 919-857-5 REACH Reg No.: 01-2119463258-33-xxxx	STOT SE 3 - H336, Asp. Tox - H304, Flam. Liq 3 - H226	15-50%
reaction mass of ?-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-?-hydroxypoly(oxyethylene) and ?-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-?-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	CAS-No.: EC No.: 400-830-7	Skin. Sens 1 - H317, Aquatic Chronic 2 - H411	1-5%
2-ethylhexanoic acid, zirconium salt	CAS-No.: 22464-99-9 EC No.: 245-018-1	Repr. 2 - H361d	0.1-0.9%
Butanone oxime	CAS-No.: 96-29-7 EC No.: 202-496-6	Acute Tox 4 - H312, Skin. Sens 1 - H317, Eye Dam. 1 - H318, Carc. 2 - H351	0.1-0.9%
Cobalt bis(2-ethylhexanoate)	CAS-No.: 136-52-7 EC No.: 205-250-6 REACH Reg No.: 01-2119524678-29-XXXX	Eye Irrit. 2A - H319, Skin. Sens 1 A - H317, Repr. 1B - H360, Aquatic Acute 1 - H400, Aquatic Chronic 3 - H412	0.1-0.9%
nonane	CAS-No.: 111-84-2 EC No.: 203-913-4	Aquatic Chronic 1 - H410, Skin Irrit. 2 - H315, Asp. Tox - H304, Flam. Liq 3 - H226, STOT SE 3 - H336	<0.1%
propionic acid	CAS-No.: 79-09-4 EC No.: 201-176-3	Skin Corr. 1B - H314	<0.1%
octane	CAS-No.: 111-65-9 EC No.: 203-892-1	Aquatic Chronic 1 - H410, Skin Irrit. 2 - H315, Asp. Tox - H304, Flam. Liq 2 - H225, STOT SE 3 - H336	<0.1%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

Propionic Acid: Specific Concentration Limits - Eye Irrit. 2; H319: 10 % ≤ C < 25 %, STOT SE 3; H335: C ≥ 10 %, Skin Corr. 1B; H314: C ≥ 25 %, Skin Irrit. 2; H315: 10 % ≤ C < 25 %.

Butanone oxime: Acute Toxicity Estimates (ATE)- dermal: ATE = 1100 mg/kg (-) oral: ATE =

100 mg/kg (-).

Section 4: First aid measures

4.1 Description of first aid measures

General information	Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue.
Inhalation	If this product is inhaled and symptoms occur, move the exposed person to fresh air promptly. If breathing is difficult, give oxygen. If breathing has stopped or the exposed person experiences difficulty in breathing, administer artificial respiration and seek immediate medical assistance.
Ingestion	Rinse mouth thoroughly. Provide fresh air, warmth and rest. Do not induce vomiting. Never give anything by mouth if victim is unconscious, is rapidly losing consciousness or is convulsing. Seek medical advice (show the label where possible). If vomiting occurs, the head should be kept low so that stomach content doesn't enter the lungs.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues after rinsing.
Eye contact	Do not rub eye. Avoid contaminating unaffected eye. Remove contact lenses if present and easy to do so. Promptly wash eye(s) with plenty of water while lifting the eye lids. Rinse with a gentle stream water for at least 15 minutes. Get prompt medical attention.

4.2 Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Exposure to product spray mists may be irritating to the respiratory system. Inhalation of vapours may cause headache, fatigue, dizziness and central nervous system effects.
Ingestion	Ingestion of large amounts of the chemical product may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	May cause temporary eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician	Treat symptomatically.
-------------------------------	------------------------

Section 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media	Use fire-extinguishing media appropriate for surrounding materials. Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet to extinguish fire.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products	During fire, gases hazardous to health may be formed.
Unusual fire & explosion hazards	The product is classified as a flammable liquid and vapour.
Specific hazards	If heated, harmful vapours may be formed.

5.3 Advice for firefighters

Special fire fighting procedures	Ventilate closed spaces before entering them. Water spray should be used to cool containers. If possible, fight fire from protected position. Keep up-wind to avoid fumes. Avoid breathing fire vapours.
Protective equipment for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection.
------------------------------------	--

For emergency responders

Wear protective clothing as described in Section 8 of this safety data sheet. If necessary evacuate surrounding areas. Eliminate all sources of ignition.

Avoid inhalation of vapours and contact with skin and eyes. Do not touch or walk through spilled material. Read and follow manufacturer's recommendations.

Follow safe handling advice and personal protective equipment recommendations for normal use of product.

6.2 Environmental precautions**Environmental precautions**

Prevent any material from entering drains or waterways.

6.3 Methods and material for containment and cleaning up**Spill clean up methods**

Wear appropriate personal protective equipment as specified in Section 8. Prevent further leakage or spillage if safe to do so. Ventilate and evacuate the area. Eliminate all sources of ignition. Dam and absorb spillage using a spill kit, sand, earth or other non-combustible material.

Prevent entry to into sewers, water course, basement or confined areas. Use non sparking tools or equipment. Recover by pumping or with suitable absorbent. Place spilled material into suitable labelled sealed containers. Remove waste promptly to a safe area.

6.4 Reference to other sections**Reference to other sections**

See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.

Section 7: Handling and storage**7.1 Precautions for safe handling****Handling**

Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Wear suitable personal protective equipment, as detailed in Section 8. Keep away from heat, sparks and open flame. Earth all equipment. Use only non-sparking tools. Avoid contact with skin and eyes. Avoid inhalation of vapours. Do not use contact lenses. Avoid prolonged or repeated contact. Read and follow manufacturer's recommendations. Keep container tightly closed.

7.2 Conditions for safe storage, including any incompatibilities**Storage precautions**

Store in tightly closed original container in a cool, dry and well-ventilated place. Keep upright, locked up and out of reach of children. Keep away from incompatible materials (see section 10). Protect against static discharge and keep away from sources of ignition.

Storage class

Flammable liquid storage.

7.3 Specific end use(s)**Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

Usage description

Use only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection**8.1 Control parameters**

Component	STD	TWA (8 Hrs)		STEL (15mins)		Notes
Butanone oxime	OEL	3 ppm	10 mg/m ³	10 ppm	33 mg/m ³	Sens
nonane	OEL	200 ppm	1050 mg/m ³			
propionic acid	OEL	10 ppm	31 mg/m ³	20 ppm	62 mg/m ³	IOELV
octane	OEL	300 ppm	1450 mg/m ³			

Ingredient comments

Ireland, Occupational Exposure Limits 2020.

8.2 Exposure Controls**Protective equipment**



Engineering measures	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.
Respiratory equipment	Use respirators and components tested and approved under appropriate government standards such as CEN (EU). Use type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.
Hand protection	Handle in accordance with good industrial hygiene and safety practices. Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374. Gloves must be selected according to the application and duration of use at the workstation. Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required. Nitrile rubber. Breakthrough time: > 480 min Layer thickness: 0.33 mm.
Eye protection	Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).
Other protection	Wear suitable protective clothing as protection against splashing or contamination. Protective clothing should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. The selected clothing must satisfy the European norm standard EN 943.
Hygiene measures	DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.
Process conditions	Ensure that eye flushing systems and safety showers are located close by in the work place.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Clear.
Odour	Hydrocarbon, (slight).
Odour threshold - lower	No information available as testing has not been completed.
Odour threshold - upper	No information available as testing has not been completed.
pH-Value, Conc. Solution	No information available as testing has not been completed.
pH-Value, Diluted solution	No information available as testing has not been completed.
Melting point	May start to solidify at the following temperature: -15°C This is based on data for the following ingredient: Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics. Weighted average: -58.56°C
Initial boiling point and boiling range	>142°C
Flash point	40.00 °C
Evaporation rate	No information available as testing has not been completed.
Flammability state	Liquid
Flammability limit - lower(%)	No information available as testing has not been completed.
Flammability limit - upper(%)	No information available as testing has not been completed.
Vapour pressure	No information available as testing has not been completed.
Vapour density (air=1)	No information available as testing has not been completed.

Relative density	0.92 +/- 0.06
Bulk density	No information available as testing has not been completed.
Solubility	Insoluble in cold water
Decomposition temperature	No information available as testing has not been completed.
Partition coefficient; n-Octanol/Water	No information available as testing has not been completed.
Auto ignition temperature (°C)	Lowest known value: >230°C (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics).
Viscosity	Kinematic (40°C): >0.27 cm ² /s
Explosive properties	Not classified as explosive.
Oxidising properties	The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight	No information available as testing has not been completed.
Volatile organic compound	372.00 g/litre
Other information	Volume solids: 51.0% +/- 1.0% Weight Solids: 59.0% +/- 1.0%

Section 10: Stability and reactivity

10.1 Reactivity

Reactivity	Reactions may occur with strong oxidising agents.
-------------------	---

10.2 Chemical stability

Stability	Stable under normal temperature conditions and recommended use.
------------------	---

10.3 Possibility of hazardous reactions

Hazardous reactions	Flammable liquid and vapour.
Hazardous polymerisation	Unknown
Polymerisation description	Unknown.

10.4 Conditions to Avoid

Conditions to avoid	Heat, sparks, open flames, temperature extremes and direct sunlight.
----------------------------	--

10.5 Incompatible materials

Materials to avoid	Do not mix with other chemicals unless listed on directions. Strong oxidising substances.
---------------------------	---

10.6 Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other harmful gases or vapors.
---	---

Section 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No. 1272/2008

Toxicological information	No toxicological information for the overall finished product.
Acute toxicity (Oral LD50)	No information available as testing has not been completed.
Acute toxicity (Dermal LD50)	No information available as testing has not been completed.

Acute toxicity (Inhalation LD50)	No information available as testing has not been completed.
Serious eye damage/irritation	May cause temporary eye irritation.
Skin corrosion/irritation	The product is not classified as a skin corrosion/irritation hazard.
Respiratory sensitisation	The product is not classified as a respiratory hazard.
Skin sensitisation	The product is classified as a skin sensitisation hazard.
Germ cell mutagenicity	The product is not classified as a mutagen.
Carcinogenicity	The product is not classified as a carcinogen hazard.
Specific target organ toxicity - Single exposure:	
STOT - Single exposure	The product is classified as a single exposure specific target organ toxin.
Specific target organ toxicity - Repeated exposure:	
STOT - Repeated exposure	The product is not classified as a repeat exposure specific target organ toxin.
Inhalation	Exposure to product spray mists may be irritating to the respiratory system. Inhalation of vapours may cause headache, fatigue, dizziness and central nervous system effects.
Ingestion	Ingestion of large amounts of the chemical product may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	May cause temporary eye irritation.
Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product.
Routes of entry	Eyes, skin, ingestion or inhalation.
Target organs	Eyes, skin, digestive system, respiratory system.
Aspiration hazards:	The product is not classified as an aspiration hazard.
Reproductive toxicity:	The product is not classified as a reproductive hazard.

Name	LD50 oral	LD50 dermal	LD50 inhalation
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	>5000.00mg/kg Rat >5000.00mg/kg Rat	3160.00mg/kg Rabbit 3160.00mg/kg Rabbit	>4950.00mg/m-3 Rat 4 Hours >4950.00mg/m-3 Rat 4 Hours
Hydrocarbons, C10-C13, n-alkanes, isalkanes, cyclics, < 2% aromatics	>5000.00mg/kg Rat >5000.00mg/kg Rat	>5000.00mg/kg Rabbit >5000.00mg/kg Rabbit	>4951.00mg/m-3 Rat 4 Hours >4951.00mg/m-3 Rat 4 Hours
reaction mass of ?-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-?-hydroxypoly(oxyethylene) and ?-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-?-hydroxypoly(oxyethylene)	>5000.00mg/kg Rat	>2000.00mg/kg Rat	>5.80mg/l (vapours) Rat 4 Hours
nonane			3200.00ppmV Rat 4 Hours 17000.00mg/m-3 Rat 4 Hours
propionic acid	2600.00mg/kg Rat	525.00mg/kg Rabbit	
octane			25260.00ppmV Rat 4 Hours 118.00g/m3 Rat 4 Hours
2-ethylhexanoic acid, zirconium salt	>5.00g/kg Rat	>5.00g/kg Rabbit	

11.2 Information on other hazards

Information on other hazards	None known.
-------------------------------------	-------------

Section 12: Ecological information

12.1 Toxicity

Acute toxicity - Fish	No information available as testing has not been completed.
Acute toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Acute toxicity - Aquatic plants	No information available as testing has not been completed.
Acute toxicity - Microorganisms	No information available as testing has not been completed.
Chronic toxicity - Fish	No information available as testing has not been completed.

Chronic toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Chronic toxicity - Aquatic plants	No information available as testing has not been completed.
Chronic toxicity - Microorganisms	No information available as testing has not been completed.
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Eco toxicological information	No ecological toxicity available on the overall finished product.

12.2 Persistence and degradability

Degradability	The degradability of the product has not been stated.
Biological oxygen demand	No information available as testing has not been completed.
Chemical oxygen demand	No information available as testing has not been completed.

12.3 Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
Bioaccumulation factor	No information available as testing has not been completed.
Partition coefficient; n-Octanol/Water	No information available as testing has not been completed.

12.4 Mobility in soil

Mobility	Insoluble in cold water.
-----------------	--------------------------

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB Substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties	The product does not contain any substances with endocrine disrupting properties at a concentration above or equal to 0.1%.
--	---

12.7 Other adverse effects

Other adverse effects	None known.
------------------------------	-------------

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	LC50 96 Hours >1000.00ppm Freshwater Fish LC50 96 Hours >1000.00ppm Freshwater Fish	EC50 48 Hours >1000.00ppm Daphnia magna EC50 48 Hours >1000.00ppm Daphnia magna	
Butanone oxime	LC50 48 Hours 560.00mg/l LC50 96 Hours 46.00mg/l Lepomis macrochirus (Bluegill)	LC50 48 Hours 750.00mg/l Daphnia magna	LC50 72 Hours 83.00mg/l
reaction mass of 3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-2-hydroxypoly(oxyethylene) and 3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	LC50 96 Hours 2.80mg/l Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours 4.00mg/l Daphnia magna	EC50 72 Hours >100.00mg/l Senastrum Capricornutum
propionic acid	LC50 96 Hours 51.00ppm Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours 22.70ppm Daphnia magna	EC50 96 Hours 43.00mg/l

Section 13: Disposal considerations

Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product.
-------------------------	--

13.1 Waste treatment methods**Disposal methods**

Dispose of waste and residues in accordance with local authority requirements. For waste disposal, use a licensed industrial waste disposal agent.

Section 14: Transport information**14.1 UN number or ID number**

UN no. (ADR)	UN1263
UN no. (IMDG)	UN1263
UN no. (IATA)	UN1263

14.2 UN proper shipping name

ADR proper shipping name	PAINT or PAINT RELATED MATERIAL
IMDG proper shipping name	PAINT or PAINT RELATED MATERIAL
IATA proper shipping name	PAINT

14.3 Transport hazard class(es)

ADR class	3
IMDG class	3
IATA class	3

Transport labels**14.4 Packing group**

ADR/RID/ADN packing group	III
IMDG packing group	III
IATA packing group	III

14.5 Environmental hazards

ADR	No
IMDG	No
IATA	No

14.6 Special precautions for user

EMS	F-E, S-E
Emergency action code	A3 A72 A192
Hazard no. (ADR)	30
Tunnel restriction code	(D/E)

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Section 15: Regulatory information**15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture**

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
Approved code of practice	2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)

15.2 Chemical safety assessment

Chemical safety assessment	No chemical safety assessment has been carried out.
-----------------------------------	---

Section 16: Other information

General information	This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.
Revision comments	This is a second issue. [1]Information updated. [2]Information updated. [3]Information updated. [4]Information updated. [5]Information updated. [8]Information updated. [9]Information updated. [10]Information updated. [11]Information updated. [12]Information updated. [15]Information updated.
Revision date	20 February 2019
Revision	2
Safety data sheet status	Approved.

Hazard statements in full

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
H361	Suspected of damaging fertility or the unborn child .
H312	Harmful in contact with skin.
H318	Causes serious eye damage.
H351	Suspected of causing cancer .
H319	Causes serious eye irritation.
H360	May damage fertility or the unborn child .
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
H315	Causes skin irritation.
H410	Very toxic to aquatic life with long lasting effects.
H314	Causes severe skin burns and eye damage.
H225	Highly flammable liquid and vapour.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.