

Technical data sheet

Coreboard	HDF swell stopp plus (emission standard E1, CARB2/TSCA VI)
Profile	CLIC it!

Declared performance according to EN 14041

Formaldehyde according to EN 717-1	E1	Slip resistance according to EN 13893	DS, $\geq 0,3$
Thermal conductivity according to EN 12524	0,12 W/(m*K)	Antistatic properties according EN 1815	yes, < 2 kV
Fire classification according to EN 13501-1	Cfl-s1		

Classification and general requirements according to EN 13329

Class of use	32
Guarantee domestic area	20 years
Guarantee commercial area	5 years
Abrasion resistance, test methode A according EN 13329, Annex E	AC4 / ≥ 4.000 cycles
Impact resistance, test methods "small/ big ball" according EN 13329, Annex H	≥ 12 N ≥ 750 mm
Resistance to staining EN 438 - 2	group 1 + 2: level 5 group 3: level 4
Thickness swelling according ISO 24336	≤ 18 %
Static indentation by constant pressure according ISO 24343-1	$\leq 0,05$ mm
Effect of furniture leg according EN 424 (foot Type 0)	No change in appearance or damage
Effect of a castor chair according EN 425	25.000 cycles
Profile strength lengthways / crossways according to ISO 24334	$\geq 1,0$ kN/m / $\geq 2,0$ kN/m
Dimensional tolerances of the board according to ISO 24337	length $\pm 0,5$ mm width $\pm 0,1$ mm thickness $\pm 0,5$ mm

Format & Packaging

Dimension mm (length x width)	Classic
	1.292 x 193
Complete thickness	12 mm
Class of use 31	
Class of use 32	✓
Class of use 33	✓
Bevel, without	
Bevel, Lengthwise	
Bevel, circumferential	✓
Bevel, circumferential + 1	
Paket information	Piece
	6
	m²
	1,50
	kg
	12,28
Pallet information	Paket per pallet
	52
	m²
	77,80
	kg
	638

